



FC-12



FC-20 / FC-25 / FC-30



EI-50





FC Stuffers

Model	Overall Height	Height to Horn	Knee Switch Height	Base Width	Base Depth	Lid Swing Radius	Capacity Litres	Capacity Lbs.
FC-20	43.6"	41.7"	24.3" to 27.8"	17.1"	21.1"	15.6"	20	45
FC-30	47.4"	45.4"	26.6" to 30.1"	19.4"	22.7"	17.3"	30	65
EI-50	49.2"	47.5"	22.6"	21.3"	21.3"	19.3"	50	105



FC-20



FC-30



FI-50

FEATURES & BENEFITS

- ALL STAINLESS CONSTRUCTION** For Durable Long Life
- STAINLESS STEEL PISTON (Optional S/S Lid on EM-20 & EM-30)** For USDA Approved Facilities
- ADJUSTABLE SIDE MOUNTED KNEE SWITCH** For More Comfortable Operation & Less Knee Strain
- POWERFUL MOTOR & OVERSIZED RAM** For Faster Stuffing with Stiff Products
- VARIABLE SPEED WITH BUILT-IN PRESSURE GAUGE** For Precise Product Control & Power (fig. 1)
- ENCLOSED OIL RESERVOIR** Eliminates Spills while Moving
- THREE STUFFING HORNS INCLUDED** For Maximum Flexibility (Choose from 10, 12, 15, 20, 25, 30 or 40 mm)
- WATER TIGHT CONSTRUCTION** For Carefree Hose-Down Cleaning
- AUTO PISTON DECOMPRESSION** For Less Overstuffing & Bleed-off when Knee Switch is Released
- REMOVABLE PISTON & SWING-OUT LID** For Easy Cleaning (fig. 2)
- SMOOTH PRODUCT DISCHARGE PATH** Eliminates Clogging & Product Discoloration
- KNEE SWITCH "AUTO-ON"** For Noise Free Idle Time (3 phase only)
- ANTI-TILT TROLLEY & CASTORS** For Safe, Stable, Easy, Strain-Free Moving (fig. 3)

OPTIONS:

- MANUAL PORTION CONTROL HEAD** For Precise Filling of Bags & Casings
- DEPOSITING "L" TUBE with FLAP VALVE** For Quick, Accurate, Drip-less Filing of Liquid Products



Manual Portion Control Head




Depositing Tube



(fig. 1)



(fig. 2)



(fig. 3)

Technical Data

Motors:
 3 Phase, 220V, 60Hz
 1 Phase, 220V, 60Hz
 1 Phase, 110V, 60Hz
 Net Weight:

Model

FC-20

FC-30

FI-50

HP / Amps
 HP / Amps
 HP / Amps
 LBS.

1.25 / 4.5
 1.50 / 10.5
 1.50 / 21.0
198

1.75 / 5.8
 2.50 / 11.5
 2.50 / 26.0
295

2.25 / 7.4
 2.50 / 11.5
 2.50 / 26.0
490



8064 Chivvis Drive
 St. Louis, MO 63123
 Fax (314) 353-6655
 (877) 677-7761

Mainca USA Inc. reserves the right to alter any specification without prior notice.



Mainca World Headquarters Barcelona, SPAIN



Mainca USA Headquarters St. Louis, MO USA

Available Exclusively
 Through Authorized
 Mainca USA Distributors